















Load wheels • Laufräder WKGK serie • Serie WKGK

Load capacity till 800kg • Tragfähigkeit bis 800kg
Wheel diameter 100<>200mm • Raddurchmesser 100<>200mm



Wheel aluminium centre with elastic vulcanised polyurethane tyre 92° Shore A : colour orange, non-marking, highly wearresistant - on precision ball bearings.
Mounted in a pressed steel castor with double ball race: zinc-plated, sealed, smoothly pivoting - types: swivel, swivel+brake, fixed.

Rad Aluminium-Radkörper mit elastischem, fest aufgegossenem Laufbelag in Polyurethan 92° Shore A: Farbe orange, nicht kreidend, sehr abriebfest - mit Präzisionskugellagern.
Montiert in einem stahlgepreßten Gehäuse mit zweireihigem Kugelkranz: glanzverzinkt, abgedichtet, leicht schwenkbar - Typen: Lenk, Lenk+Feststeller, Bock.

|            | | | | | | | | | | | |
|--|----------------|---------------|-----|----|---------|--------|-------|----|---|-----|-----|
| WK GK 100 YKN | WK GK 100 YKNS | WK GK 100 YVN | 100 | 30 | 100×85 | 80×60 | 9×12 | 36 |  | 135 | 200 |
| WK GK 125 YKN | WK GK 125 YKNS | WK GK 125 YVN | 125 | 45 | 135×110 | 105×80 | 13×16 | 45 |  | 166 | 300 |
| WK GK 160 YKN | WK GK 160 YKNS | WK GK 160 YVN | 160 | 50 | 135×110 | 105×80 | 13×16 | 57 |  | 216 | 500 |
| WK GK 200 YKN | WK GK 200 YKNS | WK GK 200 YVN | 200 | 57 | 135×110 | 105×80 | 13×16 | 57 |  | 251 | 800 |

