

Load wheels • Laufräder B-1200 serie • Serie B-1200

Load capacity till 1200kg • Tragfähigkeit bis 1200kg
Tread width 40<>80mm • Radbreite 40<>80mm



Wheel cast iron centre with elastic, firmly bonded tyre in VULKOLLAN® 92° Shore A: colour light brown, extremely wear-resistant, high load capacity - on precision ball bearings. Mounted in a heavy duty pressed steel castor with double ball race: zinc-plated, sealed, shock resistant - types: swivel, swivel+brake, fixed.

Rad Grauguß-Radkörper mit elastischem, fest aufgegossenem Laufbelag in VULKOLLAN® 92° Shore A: Farbe hellbraun, sehr abriebfest, hohe Tragfähigkeit - mit Präzisionskugellagern. Montiert in einem stahlgepreßten Schwerlastgehäuse mit zweireihigem Kugelkranz: glanzverzinkt, abgedichtet, stoßfest - Typen: Lenk, Lenk+Feststeller, Bock.

VK BK 125 UKN	VK BK 125 UKNR	VK BK 125 UVN	125	50	140x110	105x80	12	45		178	550	
VK BK 150 UKN	VK BK 150 UKNR	VK BK 150 UVN	150	50	140x110	105x80	12	52		206	700	
VK BK 200 UKN	VK BK 200 UKNR	VK BK 200 UVN	200	50	140x110	105x80	12	58		253	1000	
VK EK 200 o6o UKN	VK EK 200 o6o UKNR	VK EK 200 o6o UVN	200	60	140x110	105x80	12	58		242	1000	
VK BK 250 UKP	VK BK 250 UKPR	VK BK 250 UVP	250	50	200x160	160x120	14	85		325	1100	
VK EK 250 o6o UKP	VK EK 250 o6o UKPR	VK EK 250 o6o UVP	250	60	200x160	160x120	14	85		325	1200	

