

Load wheels • Laufräder B-2700 serie • Serie B-2700

Load capacity till 2.700kg • Tragfähigkeit bis 2.700kg
Tread width 40<>80mm • Radbreite 40<>80mm



Wheel cast iron centre with elastic, firmly bonded tyre in VULKOLLAN® 92° Shore A: colour light brown, extremely wear-resistant, high load capacity - on precision ball bearings. Mounted in a heavy duty steel welded castor with double ball race: hammer grey lacquered, sealed, shock resistant - types: swivel, swivel+brake, fixed.

Rad Grauguß-Radkörper mit elastischem, fest aufgegossenem Laufbelag in VULKOLLAN® 92° Shore A: Farbe hellbraun, sehr abriebfest, hohe Tragfähigkeit - mit Präzisionskugellagern. Montiert in einem stahlgeschweißten Schwerlastgehäuse mit zweireihigem Kugelkranz: grau Hammerschlag lackiert, abgedichtet, stoßfest - Typen: Lenk, Lenk+Feststeller, Bock.



VK BK 100 MMG	VK BK 100 MMGM	VK BK 100 MVG	100	50	130x130	105x105	10	45		144	400
VK BK 125 MMF	VK BK 125 MMFM	VK BK 125 MVF	125	40	110x110	90x90	8	45		153	350
VK BK 125 MMG	VK BK 125 MMGM	VK BK 125 MVG	125	40	130x130	105x105	10	45		156	400
VK BK 125 050 MMG	VK BK 125 050 MMGM	VK BK 125 050 MVG	125	50	130x130	105x105	10	45		168	550
VK BK 150 MMG	VK BK 150 MMGM	VK BK 150 MVG	150	50	130x130	105x105	10	45		181	700
VK BK 150 MMH	VK BK 150 MMHM	VK BK 150 MVH	150	50	150x150	125x125	10	45		188	700
VK BK 200 MMG	VK BK 200 MMGM	VK BK 200 MVG	200	50	130x130	105x105	10	65		239	750
VK BK 200 MMH	VK BK 200 MMHM	VK BK 200 MVH	200	50	150x150	125x125	10	65		241	1000
VK BK 200 MMI	VK BK 200 MMIM	VK BK 200 MVI	200	80	180x180	145x145	10	65		270	1400
VK BK 250 MMH	VK BK 250 MMHM	VK BK 250 MVH	250	50	150x150	125x125	10	50		292	1000
VK BK 250 MMI	VK BK 250 MMIM	VK BK 250 MVI	250	80	180x180	145x145	12	75		321	1400
VK EK 300 MMH	VK EK 300 MMHM	VK EK 300 MVH	300	50	150x150	125x125	10	60		348	900
VK EK 300 MNI	VK EK 300 MNIM	VK EK 300 MVI	300	50	180x180	145x145	12	75		366	1200
VK EK 300 MNJ	VK EK 300 MNJM	VK EK 300 MVJ	300	80	180x180	145x145	16	75		386	2000
VK EK 400 MTK	VK EK 400 MTKM	VK EK 400 MVK	400	80	210x210	165x165	20	75		505	2700

