
	Productspecificatie	PS-0035
	Product specification	Printdatum : 8-1-2021

Logo Logo			
Naam Name		Printhane B 85	
Afkorting Abbreviation		PB85	
Kleur Color		Natuur Natural	
Hardheid Hardness	Shore A/D	85/-	DIN 53505
Spanning bij 100% rek Stress at 100% strain	MPa	3,9	DIN 53504
Spanning bij 300% rek Stress at 300% strain	MPa	8,3	DIN 53504
Treksterkte Tensile strength	MPa	52	DIN 53504
Rek bij breuk Elongation at break	%	560	DIN 53504
Doorscheurweerstand (Graves) Tear propagation resistance	kN/m	48	DIN 53515
Rebound Rebound	%	51	DIN 53512
Abrasieweerstand Abrasion resistance	mm ³	40	DIN 53516
Soortelijk gewicht Density	g/cm ³	1,24	DIN 53479
Drukvervormingsrest Compression set	%		DIN 53517
	70 h / 23°C 70 h / 73.5°F	27	
	24 h / 70°C 24 h / 158°F	55	

De productspecificaties zijn op basis van metingen op proefstukken vastgelegd en zijn daarom niet als productiespecificaties te beschouwen.

De eigenschappen gemeten op productie onderdelen kunnen afwijken van de eigenschappen gemeten op labo proefstukken, daar de correcte proefstuk productie uit productieonderdelen niet steeds gegarandeerd kan worden.

The productspecifications are obtained by measurement on test specimens and are not to be interpreted as production specifications. The measurements made on production parts can differ from those made on test specimens as the correct production of a test specimen out of a production part is not always guaranteed.

OPGESTELD : BMA	GOEDGEKEURD : BMA
-----------------	-------------------